

Cobra Radial G/T



The Cobra Radial G/T is Cooper's all-season cosmetic performance tyre that is targeted at buyers who prefer raised white-letter styling in an all-season tyre.

The Cobra Radial G/T is especially popular with drivers of older domestic "muscle cars" who still want to retain the characteristic "look" of their vehicle.

Please note these tyres are ordered on request.
Write to info@coopertyres.co.za

PERFORMANCE TREAD

Increased tyre-to-road contact which leads to improvements in treadwear and handling.

EVEN WEARING DESIGN

The notches, solid centre rib, along with a refined tread element shape, helps provide even treadwear. Shoulder-slotting is also designed for resistance to irregular wear while providing solid, all-season performance.

SIDEWALL AND SIZE OPTIONS

Available in a full selection of popular sizes, the Cobra G/T offers a unique, stylised, raised white letter sidewall to enhance vehicle appearance. The reverse side offers a serrated, black letter look for a more subtle effect. Some sizes are available in black lettering, only featuring a reversible option: stylised sidewall on one side and a traditional, smooth sidewall with standard lettering on the reverse.

POLY / STEEL CONSTRUCTION

Low stretch polyester plies along with strong steel cord belts provide a tough tyre body for excellent durability.

Cobra Radial G/T

Product Code	Tyre Size	RF/XL	Index	Sdwl.	Approved Rim Recommended Width	Approved Rim Min Width	Approved Rim Max Width	Pass Max Load (kg)	Overall Diam. (mm)
1139608	235/60R14		96T	RWL	7.0	6.5	8.5	710	637
1139633	215/70R14		96T	RWL	6.5	5.5	7.0	705	654
1139634	225/70R14		98T	RWL	6.5	6.0	7.5	760	667
39602	295/50R15		105S	RWL	9.5	8.0	10.0	935	681
1139612	235/60R15		98T	RWL	7.0	6.5	8.5	745	663
1139613	245/60R15		100T	RWL	7.0	7.0	8.5	795	674
1139614	255/60R15		102T	RWL	7.5	7.0	9.0	855	686
39616	215/65R15		95T	RWL	6.5	6.0	7.5	685	660
39636	225/70R15		100T	RWL	6.5	6.0	7.5	795	695
39637	235/70R15		102T	RWL	7.0	6.0	8.0	860	709
39638	255/70R15		108T	RWL	7.5	6.5	8.5	990	735
39650	235/55R16		96T	BLK	7.5	6.5	8.5	710	664



ALWAYS CONSULT AND FOLLOW THE VEHICLE MANUFACTURERS' REPLACEMENT TYRE RECOMMENDATIONS AND WARNINGS.
Use the information on the vehicle placard and in the vehicle owners manual to identify original equipment air pressure, tyre size, speed rating and load capacity.
Cooper reserves the right to change and improve construction, materials or specifications without notice or obligation.
Contact info@coopertyres.co.za for current information.

Zeon CS SPORT



The Cooper Zeon CS Sport is the latest addition to the ultra high performance range.

Packed with new design features, the CS Sport is orientated towards the driving enthusiast, delivering supreme performance while maximising the driving experience.

HIGH DISPERSION SILICA TREAD

Provides improved wet performance as well as excellent traction in dry conditions.

0° SPIRAL RESTRICTOR

Improved high speed performance.

2 PLY RAYON CASING

Tuned construction for exceptionally crisp, predictable handling.

FLIPPER REINFORCEMENT

Improved steering response and lateral stability.

TRI-ARC MOULD PROFILE

Developed for improved contact pressure distribution handling and balanced treadwear.

DESIGNED AND DEVELOPED WITH THE DRIVING ENTHUSIAST IN MIND

A select range of 18" and 19" sizes W and Y speed ratings.

Zeon CS Sport

Product Code	Tyre Size	RF/XL	Index	Approved Rim Recommended Width	Approved Rim Min Width	Approved Rim Max Width	Pass Max Load (kg)	Overall Diam. (mm)
5170096	225/40R18	XL	92Y	8.0	7.5	9.0	630	637
5170092	245/45R18	XL	97Y	8.5	8.0	9.5	730	653
5170097	255/35R18	XL	94Y	9.0	8.5	10.0	670	635
5170098	235/35R19	XL	91Y	8.5	8.0	9.5	615	647
5170291	245/40R19	XL	98Y	8.5	8.0	9.5	750	679
5170099	255/35R19	XL	96Y	9.0	8.5	10.0	710	661
5170197	225/45R18	XL	95Y	7.5	7.0	8.5	690	659
5170013	235/40R18		91Y	8.5	8.0	9.5	615	645
5170094	235/40R18	XL	95Y	8.5	8.0	9.5	690	645
5170190	245/45R18	XL	100W	8.0	7.5	9.0	800	677
5170198	235/45R18	XL	98Y	8.5	8.0	9.0	750	669
5170290	255/45R18	XL	103Y	8.5	8.0	9.5	875	687
5170119	255/45R18		99Y	8.5	8.0	9.5	775	687



ALWAYS CONSULT AND FOLLOW THE VEHICLE MANUFACTURERS' REPLACEMENT TYRE RECOMMENDATIONS AND WARNINGS.
 Use the information on the vehicle placard and in the vehicle owners manual to identify original equipment air pressure, tyre size, speed rating and load capacity.
 Cooper reserves the right to change and improve construction, materials or specifications without notice or obligation.
 Contact info@coopertyres.co.za for current information.

Zeon CS8



The new Cooper Zeon CS8 high performance passenger tyre brings unprecedented “A” grade wet grip, handling and fuel efficiency. This tyre provides wet performance as well as excellent traction in dry conditions with its high dispersion silica tread. Noise damping structures reduce airborne noise generated by the tyre/road interaction. Wear Square™ visual indicator allows a quick check on approximate tread life remaining on the tyre and indicates any potential wheel alignment issues with the vehicle.

NOISE DAMPING STRUCTURES

Reduces airborne noise generated by the tyre/road interaction.

HIGH DISPERSION SILICA TREAD

Provides improved wet performance as well as excellent traction in dry conditions.

WEAR SQUARE™ VISUAL INDICATOR

The Wear Square visual indicator allows you and your customer to quickly see the approximate tread life remaining on the tyres. As the tyre wears, the shape of the Wear Square will also change. The five stages begin with a square at new and end with an exclamation mark when the tread reaches 1.59mm, indicating it is time to replace the tyres. The Wear Square is located on the inside and outside half of the tyre. Upon inspection, if the inner and outer Wear Squares are at different stages, this indicates uneven tyre wear and a possible wheel alignment issue with the vehicle.

FUNCTIONAL RIM FLANGE PROTECTORS

In all sizes help protect against kerb damage.

3D MICRO-GAUGE™

The tread pattern features 3D sipes with interlocking three dimensional points. These help the tyre warm up and provide enhanced wet grip.

ASYMMETRICAL PROFILE

It features sequenced tread blocks to reduce generated noise, whilst dimples in the tread grooves mean a quieter ride. Available in 16” to 18” rim diameters with V, W and Y speed ratings.

Zeon CS8

Product Code	Tyre Size	RF/XL	Index	EU Rating	Sdwl.	Approved Rim Recommended Width	Approved Rim Min Width	Approved Rim Max Width	Overall Diam. (mm)
S350016	195/65R15		91V	E A69))	BSW	6.0	5.5	7.0	635
S350017	205/65R15		94V	E A69))	BSW	6.0	5.5	7.5	647
S350011	195/60R15		88V	E A69))	BSW	6.0	5.5	7.0	615
S350012	205/60R15		91V	E A69))	BSW	6.0	5.5	7.5	627
S350018	185/55R15		82V	E A68))	BSW	6.0	5.0	6.5	585
S350019	195/55R15		85V	C A69))	BSW	6.0	5.5	7.0	595
S350013	205/60R16		92V	C A69))	BSW	6.0	5.5	7.5	652
S350095	215/60R16	XL	99V	C A70))	BSW	6.5	6.0	7.5	664
S350110	195/55R16		87V	E A69))	BSW	6.0	5.5	7.0	620
S350111	205/55R16		91V	C A69))	BSW	6.5	5.5	7.5	632
S350214	205/55R16		91W	C A69))	BSW	6.5	5.5	7.5	632
S350296	205/55R16	XL	94W	C A70))	BSW	6.5	5.5	7.5	632
S350114	215/55R16		93V	C A69))	BSW	7.0	6.0	7.5	642
S350217	215/55R16		93W	C A69))	BSW	7.0	6.0	7.5	642
S350297	215/55R16	XL	97W	C A70))	BSW	7.0	6.0	7.5	642
5350092	225/55R16	XL	99W	C A70))	BSW	7.0	6.0	8.0	654
5350192	225/55R16	XL	99Y	C A70))	BSW	7.0	6.0	8.0	654
S350197	195/50R16	XL	88V	E A70))	BSW	6.0	5.5	7.0	602
S350118	205/50R16		87V	E A69))	BSW	6.5	5.5	7.5	612
S350298	205/50R16		87W	E A69))	BSW	6.5	5.5	7.5	612
S350312	225/50R16		92W	C A69))	BSW	7.0	6.0	8.0	632
S350291	195/45R16	XL	84V	E A70))	BSW	6.5	6.0	7.5	582
S350313	205/45R16		83W	E A69))		7.0	6.5	7.5	590
S350394	205/45R16	XL	87W	E A70))	BSW	7.0	6.5	7.5	590
S350213	215/45R16	XL	90V	C A69))	BSW	7.0	7.0	8.0	600
5350011	215/55R17		94W	C A69))	BSW	7.0	6.0	7.5	668
5350013	225/55R17		97W	C A69))	BSW	7.0	6.0	8.0	680
5350094	225/55R17	XL	101W	C A70))	BSW	7.0	6.0	8.0	680
5350113	225/55R17		97Y	C A69))	BSW	7.0	6.0	8.0	680
S350119	205/50R17		89V	E A69))	BSW	6.5	5.5	7.5	638
S350299	205/50R17	XL	93W	C A70))	BSW	6.5	5.5	7.5	638
S350310	215/50R17		91W	E A69))	BSW	7.0	6.0	7.5	648
S350391	215/50R17	XL	95W	C A70))	BSW	7.0	6.0	7.5	648
5350290	225/50R17	XL	98V	C A70))	BSW	7.0	6.0	8.0	658
5350095	225/50R17	XL	98W	C A70))	BSW	7.0	6.0	8.0	658
5350194	225/50R17	XL	98Y	C A70))	BSW	7.0	6.0	8.0	658
S350292	205/45R17	XL	88V	C A70))	BSW	7.0	6.5	7.5	616



ALWAYS CONSULT AND FOLLOW THE VEHICLE MANUFACTURERS' REPLACEMENT TYRE RECOMMENDATIONS AND WARNINGS.
 Use the information on the vehicle placard and in the vehicle owners manual to identify original equipment air pressure, tyre size, speed rating and load capacity.
 Cooper reserves the right to change and improve construction, materials or specifications without notice or obligation.
 Contact info@coopertyres.co.za for current information.

Zeon CS8

Product Code	Tyre Size	RF/XL	Index	EJ Rating	Sdwl.	Approved Rim Recommended Width	Approved Rim Min Width	Approved Rim Max Width	Overall Diam. (mm)
5350395	205/45R17	XL	88W	C A70))	BSW	7.0	6.5	7.5	616
5350096	215/45R17	XL	91W	C A70))	BSW	7.0	7.0	8.0	626
5350196	215/45R17	XL	91Y	C A70))	BSW	7.0	7.0	8.0	626
5350294	225/45R17	XL	94V	C A70))	BSW	7.5	7.0	8.5	634
5350017	225/45R17		91W	E A69))	BSW	7.5	7.0	8.5	634
5350117	225/45R17		91Y	E A69))	BSW	7.5	7.0	8.5	634
5350198	225/45R17	XL	94Y	C A70))	BSW	7.5	7.0	8.5	634
5350099	235/45R17	XL	97W	C A70))	BSW	8.0	7.5	9.0	644
5350195	245/45R17	XL	99Y	C A70))	BSW	8.0	7.5	9.0	652
5350210	245/40R17		91Y	C A69))	BSW	8.5	8.0	9.5	628
5350190	225/40R18	XL	92W	C A70))	BSW	8.0	7.5	9.0	637
S350094	205/60R16	XL	96V	C A70))	BLK	6.00	5.5	7.5	652
5350115	225/55R16		95V	C A69))	BSW	7.0	6.0	8.0	654



ALWAYS CONSULT AND FOLLOW THE VEHICLE MANUFACTURERS' REPLACEMENT TYRE RECOMMENDATIONS AND WARNINGS.
 Use the information on the vehicle placard and in the vehicle owners manual to identify original equipment air pressure, tyre size, speed rating and load capacity.
 Cooper reserves the right to change and improve construction, materials or specifications without notice or obligation.
 Contact info@coopertyres.co.za for current information.